

	Search Text	DBs	Time Stamp
18	carborundum and rubber	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:53
19	(carborundum and rubber) and tire	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:53
20	((carborundum and rubber) and tire) and tread	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 14:01
21	(524/493).CCLS.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 14:02
22	(524/492).CCLS.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 14:03
23	(524/496).CCLS.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 14:04
24	(524/495).CCLS.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 14:04
25	(524/430).CCLS.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 14:05
26	(524/438).CCLS.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 14:06
27	(rubber and (silicon adj carbide)) and tire	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 14:06
28	("6121346").PN.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 14:06
29	((("6121346").PN.) and (silicon adj carbide)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 14:07
30	tacktene near3 (vinyl)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/21 09:17

	Search Text	DBs	Time Stamp
1	tire and tread and ((silicon adj carbide) near10 (BET and (particle adj size)))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/21 09:17
2	tire and ((silicon adj carbide) near10 (BET and (particle adj size)))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:26
3	((silicon adj carbide) near10 (BET and (particle adj size)))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:27
4	rubber and (silicon adj carbide)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:27
5	silicon carbide and BET and particle size	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:28
6	silicon carbide and BET and (particle adj size)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:28
7	(silicon adj carbide) and BET and (particle adj size)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:28
8	(silicon adj carbide) same (BET and (particle adj size))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:33
9	wyrozebski and (silicon adj carbide)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:34
10	wyrozebski	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:34
11	((silicon adj carbide) same (BET and (particle adj size))) and rubber	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:34
12	wyrozebski and (silicon adj carbide)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:36
13	rubber and (silicon adj carbide)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:36
14	(rubber and (silicon adj carbide)) and tire	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:36
15	((rubber and (silicon adj carbide)) and tire) and tread	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:44
16	carborundum	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:53
17	SiC adj PT8026J	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/11/20 13:53

NanoProducts Corporation focuses on materials nanotechnology. We work on developing and applying nanoscale building blocks for performance-enhanced products. In other words, our goal is to significantly enhance the productivity and profitability by delivering nano-engineered forms of materials used in products and processes.

Duradene A.O.		Bound Styrene	Block Styrene	Vinyl Tg	Base ML/4	OE ML/4	Oil PHR	Oil Type	Specific Gravity
706	N.S.	23.5	<2	11 - 62	55	--	0	--	0.93
707*	N.S.	23.5	<1	11 - 62	45	--	0	--	0.93
711	S.S.	18.0	<1	11 - 70	70	--	0	--	0.93
715	S.S.	23.5	<1	46 - 39	60	--	0	--	0.94
750	S.	18.0	<1	11 - 70	103	45	37.5	ARO.	0.94
751	S.	25.0	<1	11 - 60	110	45	37.5	ARO.	0.95
753	S.	33.0	<1	13 - 50	145	74	20.0	ARO.	0.95
756	S.	33.5	<1	30 - 39	125	57	37.5	ARO.	0.95
758	N.S.	25.0	<1	11 - 60	103	45	37.5	NAP.	0.94
762	S.	40.0	<1	36 - 27	140	63	37.5	ARO.	0.96

**Not currently in production*

Contact our Akron Technical Service Group for any of your formulating and development needs by using the [contact form](#) or call 800-282-0222.

[Home](#) | [Product Applications](#) | [Sales Offices](#) | [Contact Us](#)

© 1996-2001 · Firestone Polymers · 381 W. Wilbeth Road, Akron, OH 44301 · 800-282-0222 ·

Taktene® (Tire Products)**Butadiene rubber(BR)****Properties:**

- Provided that the compounds are formulated and processed correctly, the vulcanizates have good resistance to aging, reversion, abrasion and flex cracking, good low temperature flexibility and high resilience.

Applications:

- Tires, conveyor belting, caterpillar tread blocks, footwear soles, V-belts; blended with NR for goods having thick sections and needing high resistance to reversion, e.g. buffers, roll covers needing high abrasion resistance; seals, profiles and other goods, particularly those produced by injection molding

Food contact:

•

Product	Catalyst	Cis-1,4 content (%)	Oil content (wt %)	Mooney viscosity (ML (1+4) 100°C)	Remarks
▼ Masterbatch with 77 pbw N 234 black					
<u>Taktene® 1359</u>	cobalt	> 96	23 +/- 2	59 +/- 7*	*Different measuring method: MS (1+4) 100°C
▼ Standard grades					
<u>Taktene® 1203</u>	cobalt	> 96	-	43 +/- 5	
<u>Taktene® 1203-G1</u>	cobalt	> 96	-	43 +/- 5	
<u>Taktene® 1220</u>	cobalt	> 96	-	41 +/- 5	
<u>Taktene® 220</u>	cobalt	> 96	-	40 +/- 5	
<u>Taktene® 221</u>	cobalt	> 96	-	53 +/- 5	
<u>Taktene® 4510</u>	lithium	38	-	45 +/- 5	
<u>Taktene® 5510</u>	lithium	38	-	53 +/- 6	

Product Specification

Fibers, Additives and
Rubber Division

Rubber

TAKTENE 1203*

Product Description

A highly linear, low Mooney viscosity, non-staining, solution polymerized, high cis-1,4-polybutadiene rubber.

Raw Polymer Properties

Property	Range	Test Method
Mooney viscosity ML 1+4(100°C)	43 ± 5	ASTM D 1646
Volatile matter (wt %)	0.7 max.	ASTM D 5668

Cure ⁽¹⁾⁽²⁾ Characteristics

Property	Range	Test Method
Minimum torque ML (dN.m) (lbf.in)	3.7 ± 1.0 3.3 ± 0.9	ASTM D 5289 ASTM D 5289
Maximum torque MH (dN.m) (lbf.in)	20.4 ± 3.0 18.1 ± 2.7	ASTM D 5289 ASTM D 5289
tS1 (minutes)	2.3 ± 1.2	ASTM D 5289
t'50 (minutes)	7.8 ± 1.3	ASTM D 5289
t'90 (minutes)	11.7 ± 2.1	ASTM D 5289

Other Product Features

Property	Typical Value
Specific gravity	0.91
Stabilizer type	Non-staining

(1) MDR Rheometer at 160°C, ±0.5 degree arc, 30 minutes running time, no preheat

(2) Cure characteristics determined on the following MIM mixed compound:

TAKTENE 1203	100	(parts by mass)
Zinc oxide	3	
Stearic acid	2	
IRB #7 black (N330)	60	
Naphthenic oil	15	
TBBS	0.9	
Sulfur	1.5	

* This specification refers to product manufactured by Bayer Inc.,
Sarnia, Ontario, Canada.

Date of Issue: October 1, 1999
Previous Issue: January 1, 1999

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. This application-specific analysis at least must include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done by Bayer Corporation. All information is given without warranty or guarantee. It is expressly understood and agreed that customer assumes and hereby expressly releases Bayer Corporation from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance and information. Any statement or recommendation not contained herein is unauthorized and shall not bind Bayer Corporation. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or its use. No license is implied or in fact granted under the claims of any patent.